

# NJIT Physics 121 Formula Sheet

## Fundamentals

Electron:	$e = -1.6 \times 10^{-19} \text{ C}, m_e = 9.11 \times 10^{-31} \text{ kg}$
Proton:	$m_p = 1.67 \times 10^{-27} \text{ kg}$
Number of excess electrons:	$N =  Q /e$
Electromagnetic constants:	$\epsilon_0 = 8.85 \times 10^{-12} \text{ C}^2/(\text{N}\cdot\text{m}^2)$ $1/(4\pi\epsilon_0) = k = 9 \times 10^9 \text{ (N}\cdot\text{m}^2)/\text{C}^2$ $\mu_0 = 4\pi \times 10^{-7} \text{ T}\cdot\text{m/A}$
Acceleration due to gravity:	$g = 9.8 \text{ m/s}^2$

## Preliminaries: Vectors, General Mathematics

Vector magnitude:	$ \vec{A}  = \sqrt{A_x^2 + A_y^2} \text{ or } \sqrt{A_x^2 + A_y^2 + A_z^2}$
Vector direction:	$\tan \theta = \frac{A_y}{A_x}$
Dot product:	$\vec{A} \cdot \vec{B} = A_x B_x + A_y B_y + A_z B_z =  \vec{A}   \vec{B}  \cos \theta$
Cross product:	$\hat{i} \times \hat{j} = \hat{k} \quad \hat{j} \times \hat{k} = \hat{i} \quad \hat{k} \times \hat{i} = \hat{j}$ $\hat{i} \times \hat{i} = \hat{j} \times \hat{j} = \hat{k} \times \hat{k} = 0$ $\vec{A} \times \vec{B} = (A_y B_z - A_z B_y) \hat{i} + (A_z B_x - A_x B_z) \hat{j} + (A_x B_y - A_y B_x) \hat{k}$ $ \vec{A} \times \vec{B}  =  \vec{A}   \vec{B}  \sin \theta$
Quadratic formula:	$ax^2 + bx + c = 0, x = (-b \pm \sqrt{b^2 - 4ac}) / (2a)$
Integrals:	$\int dx/x = \ln x; \int dx/\sqrt{a^2 + x^2} = \ln(x + \sqrt{a^2 + x^2})$ $\int dx (a^2 + x^2)^{-\frac{3}{2}} = x / (a^2 \sqrt{a^2 + x^2})$ $\int x (a^2 + x^2)^{-\frac{3}{2}} dx = -1/\sqrt{a^2 + x^2}$
Circumference:	$C = 2\pi R$
Sphere area, volume:	$A = 4\pi R^2, V = \frac{4}{3}\pi R^3$
Cylinder and cone volume:	$V = \pi R^2 h \text{ (cylinder)}, V = \frac{1}{3}\pi R^2 h \text{ (cone)}$

## Physics 111

Kinematics:	$v_f = v_0 + at$ $\Delta x = v_0 t + \frac{1}{2}at^2$ $v_f^2 = v_0^2 + 2a\Delta x$ $v_f + v_0 = 2\Delta x/t$
Newton's Laws:	$\vec{F}_{\text{net}} = 0 \longleftrightarrow \vec{v} = \text{constant}$ $\vec{F}_{\text{net}} = m\vec{a}$ $\vec{F}_{12} = -\vec{F}_{21}$
Uniform circular motion	$\omega = v/R, a_c = v^2/R = \omega^2 R$
Work and power:	$W = \int_a^b \vec{F} \cdot d\vec{r}, P = W/t = \vec{F} \cdot \vec{v}$
Kinetic energy:	$K = \frac{1}{2}mv^2$
Work-Energy Theorem	$\Delta K = W_{\text{net}}$
Potential energy (conservative forces):	$W_{ab} = U_a - U_b = -\Delta U$

## Chapter 21: Electric Charge and the Electric Field

Coulomb's Law:	$\vec{F} = \frac{1}{4\pi\epsilon_0} \frac{q_1 q_2}{r^2} \hat{r}$
Force on a test charge $q_0$ :	$\vec{F} = q_0 \vec{E}$
Field of a point charge:	$\vec{E} = \frac{1}{4\pi\epsilon_0} \frac{q}{r^2} \hat{r}$
Charge density:	$\lambda = Q/L \text{ (linear)}$ $\sigma = Q/A \text{ (area)}$ $\rho = Q/V \text{ (volume)}$
Field of an infinite line of charge:	$E = \frac{\lambda}{2\pi\epsilon_0 r}$
Field of an infinite nonconducting plane of charge:	$E = \frac{\sigma}{2\epsilon_0}$

## Chapter 22: Gauss's Law

Flux of a uniform field through a flat surface:	$\Phi_E = EA \cos \phi$
Flux of a nonuniform field:	$\Phi_E = \oint \vec{E} \cdot d\vec{A}$
Gauss's Law:	$\oint \vec{E} \cdot d\vec{A} = \frac{Q_{\text{enc}}}{\epsilon_0}$
Field at the surface of a conductor:	$E = \frac{\sigma}{\epsilon_0}$
Solid insulating sphere, radius $R$ , with charge $Q$ distributed uniformly throughout volume:	$E = \frac{1}{4\pi\epsilon_0} \frac{Q}{r^2} \text{ (outside, } r > R)$ $E = \frac{1}{4\pi\epsilon_0} \frac{Qr}{R^3} \text{ (inside, } r < R)$

## 23: Electric Potential

Potential energy, two charges:	$U = \frac{1}{4\pi\epsilon_0} \frac{qq_0}{r}$
Electric potential:	$V = U/q_0$
Potential of a point charge:	$V = \frac{1}{4\pi\epsilon_0} \frac{q}{r}$
Superposition:	$V = \frac{1}{4\pi\epsilon_0} \sum_i \frac{q_i}{r_i}$
Charge distribution:	$V = \frac{1}{4\pi\epsilon_0} \int \frac{dq}{r}$
Work:	$W_{ab} = U_a - U_b = -q\Delta V$
Potential from field:	$V_a - V_b = \int_a^b \vec{E} \cdot d\vec{l}$
Constant field:	$\Delta V = -Ed$
Field from potential:	$E_x = -\partial V/\partial x, E_y = -\partial V/\partial y, E_z = -\partial V/\partial z$
Conducting sphere, radius $R$ and charge $Q$ :	$V(r) = kQ/r \text{ (} r > R)$ $V(r) = kQ/R \text{ (} r \leq R)$

## Chapter 24: Capacitance and Dielectrics

Field at a conductor:  $E = \sigma/\epsilon_0$   
Field between two oppositely charged plates ( $\sigma$  and  $-\sigma$ ):  $E = \sigma/\epsilon_0$   
Parallel-plate capacitor:  $C = Q/V = K\epsilon_0 A/d$   
Energy in a capacitor:  $U = \frac{1}{2}CV^2 = \frac{1}{2}Q^2/C = \frac{1}{2}QV$   
Capacitors in parallel:  $C_{\text{eq}} = C_1 + C_2 + \dots$   
Capacitors in series:  $1/C_{\text{eq}} = 1/C_1 + 1/C_2 + \dots$   
Total charge:  $Q = C_{\text{eq}}V$

## Chapter 25: Current, Resistance, and Electromotive Force

Electric current:  $I = dq/dt$  or  $\Delta q/\Delta t$   
Current density:  $J = I/A = nqv_d$   
Resistivity:  $\rho = E/J$   
Resistance (cylindrical conductor):  $R = \rho L/A$   
Ohm's Law:  $V = IR$   
Source with internal resistance:  $V_{ab} = \mathcal{E} - Ir$   
Power (general):  $P = V_{ab}I$   
Power delivered to a resistor:  $P = VI = I^2R = V^2/R$

## Chapter 26: DC Circuits

Resistors in series:  $R_{\text{eq}} = R_1 + R_2 + \dots$   
Resistors in parallel:  $1/R_{\text{eq}} = 1/R_1 + 1/R_2 + \dots$   
Kirchoff's Rules:  $\Sigma I = 0$  (node),  $\Sigma V = 0$  (loop)  
RC circuit, time constant:  $\tau = RC$   
RC circuit, capacitor charging:  $q(t) = \mathcal{E}C(1 - e^{-t/\tau})$   
 $= q_F(1 - e^{-t/\tau})$   
 $V(t) = q(t)/C = \mathcal{E}(1 - e^{-t/\tau})$   
 $i(t) = i_{\text{max}}e^{-t/\tau}$ ,  $i_{\text{max}} = \mathcal{E}/R$   
RC circuit, capacitor discharging:  $q(t) = Q_0e^{-t/\tau}$   
 $V(t) = V_0e^{-t/\tau}$ ,  $V_0 = Q_0/C$   
 $i(t) = I_0e^{-t/\tau}$ ,  $I_0 = Q_0/\tau$

## Chapter 27: Magnetic Fields and Magnetic Forces

Magnetic force:  $\vec{F} = q\vec{v} \times \vec{B}$   
Motion in a magnetic field:  $R = \frac{mv}{|q|B}$ ,  $T = \frac{2\pi m}{|q|B}$   
Magnetic flux:  $\Phi_B = \int \vec{B} \cdot d\vec{A}$  or  $\Phi_B = BA$   
Force on a current-carrying segment:  $d\vec{F} = Id\vec{l} \times \vec{B}$   
Force on a current-carrying wire:  $\vec{F} = I\vec{L} \times \vec{B}$   
Magnetic moment of a loop:  $\vec{\mu} = I\vec{A}$   
Torque on a current-carrying loop:  $\tau = IBA \sin \phi$   
Potential energy of a loop:  $U = -\vec{\mu} \cdot \vec{B}$

## Chapter 28: Sources of Magnetic Field

Field of a moving charge:  $\vec{B} = \frac{\mu_0}{4\pi} \frac{q\vec{v} \times \hat{r}}{r^2}$   
Field of a current-carrying element:  $d\vec{B} = \frac{\mu_0}{4\pi} \frac{Id\vec{l} \times \hat{r}}{r^2}$   
Field of a current-carrying wire:  $B = \frac{\mu_0 I}{2\pi r}$   
Force between wires:  $\frac{F}{L} = \frac{\mu_0 I_1 I_2}{2\pi r}$   
Field at the center of a loop:  $B = \frac{\mu_0 I}{2a}$   
Field on the axis of a solenoid:  $B = \mu_0 nI$ ,  $n$  = turns per unit length  
Ampere's Law:  $\oint \vec{B} \cdot d\vec{l} = \mu_0 I_{\text{encl}}$

## Chapter 29: Electromagnetic Induction

Faraday's Law:  $\mathcal{E} = -d\Phi_B/dt$   
 $= -A dB/dt$  (constant area, varying field)  
 $= -B dA/dt$  (constant field, varying area)  
Induced current:  $I_{\text{ind}} = \mathcal{E}/R$   
Motional EMF  $\mathcal{E} = vBL$  (constant field)  
 $= \oint (\vec{v} \times \vec{B}) \cdot d\vec{l}$  (if  $\vec{B} = B\vec{r}(r)$ )  
Induced electric fields:  $\oint \vec{E} \cdot d\vec{l} = -d\Phi_B/dt$

## Chapter 30: Inductance

Inductance of a loop:  $L = \Phi_B/i$   
Solenoid (length  $l$ , area  $A$ , density  $n$ ):  $L = \mu_0 An^2 l$   
Induced emf:  $\mathcal{E} = -L di/dt$   
Magnetic field energy:  $U = \frac{1}{2}LI^2$   
RL circuit time constant:  $\tau = L/R$   
RL circuit current:  $i(t) = \mathcal{E}/R(1 - e^{-t/\tau})$   
LC circuit:  $\omega = 2\pi f = 1/\sqrt{LC}$   
LC circuit energy:  $\frac{1}{2}Q_{\text{max}}^2/C = \frac{1}{2}LI_{\text{max}}^2$   
LRC circuit:  $\omega' = \sqrt{\frac{1}{LC} - \frac{R^2}{4L^2}}$

## Chapter 31: Alternating Current

rms current, voltage:  $I_{\text{rms}} = I/\sqrt{2}$ ,  $V_{\text{rms}} = V/\sqrt{2}$   
Inductive and capacitive reactance:  $X_L = \omega L$ ,  $X_C = 1/\omega C$   
Impedance:  $Z = \sqrt{R^2 + (X_L - X_C)^2}$   
Current amplitude:  $I = \mathcal{E}/Z$   
Phase angle:  $\tan \phi = (X_L - X_C)/R$   
Resonance:  $\omega_d = \omega_0 = 1/\sqrt{LC}$   
 $X_L = X_C$  and  $Z = R$  = minimum  
current = maximum