

NJIT Physics 102 Formula Sheet

Chapter 1: Mathematics Formulas, Unit Conversions

Quadratic formula: $ax^2 + bx + c = 0$, $x = (-b \pm \sqrt{b^2 - 4ac}) / (2a)$
 Unit conversions: 1 mile = 5,280 ft = 1.609 km
 1 inch = 2.54 cm
 1 kg = 2.2 lbs

Chapter 2: One-Dimensional Motion

Displacement: $\Delta x = x_f - x_0$
 Constant velocity: $x_f = x_0 + vt$ or $\Delta x = vt$
 Constant acceleration: $v_f = v_0 + at$
 $\Delta x = v_0 t + \frac{1}{2}at^2$
 $v_f^2 = v_0^2 + 2a\Delta x$
 $v_f + v_0 = 2\Delta x / t$
 $\Delta x = v_f t - \frac{1}{2}at^2$
 Average velocity: $v_{\text{avg}} = (x_f - x_0) / (t_f - t_0)$
 Average speed: speed = (total distance) / (elapsed time)
 Average acceleration: $a_{\text{avg}} = (v_f - v_0) / (t_f - t_0)$
 Acceleration due to gravity: $g = 9.8 \text{ m/s}^2$

Chapter 3: Vectors and Two-Dimensional Motion

Vector magnitude: $|\vec{A}| = \sqrt{A_x^2 + A_y^2}$ or $\sqrt{A_x^2 + A_y^2 + A_z^2}$
 Vector direction: $\theta = \tan^{-1} \frac{A_y}{A_x}$, add 180° if necessary
 Vector components: $A_x = |\vec{A}| \cos \theta$
 $A_y = |\vec{A}| \sin \theta$
 Projectile motion, horizontal: $\Delta x = v_{0,x} t$
 Projectile motion, vertical: $v_{f,y} = v_{0,y} + at$
 $\Delta y = v_{0,y} t + \frac{1}{2}at^2$
 $v_{f,y}^2 = v_{0,y}^2 + 2a\Delta y$
 $\Delta y = v_{f,y} t - \frac{1}{2}at^2$
 Projectile range: $R = v^2 \sin(2\theta) / g$

Chapter 4: Forces

First Law: $\vec{F}_{\text{net}} = 0 \longleftrightarrow$ constant velocity
 Second Law: $\vec{F}_{\text{net}} = m\vec{a}$
 Third Law: $\vec{F}_{12} = -\vec{F}_{21}$
 Kinetic and static friction: $f_k = \mu_k F_N$ and $f_s \leq \mu_s F_N$
 Normal force: $F_N = mg$ on horizontal surface,
 $F_N = mg \cos \theta$ on incline
 (in the absence of other forces)

Chapter 5: Circular Motion

speed: $v = 2\pi r / T$
 RPM: $v = \text{RPM's} \times 2\pi r / 60$
 Radial acceleration: $a_{\text{rad}} = v^2 / r$ or $4\pi^2 r / T^2$
 Nonuniform motion: $|a_{\text{tot}}| = \sqrt{a_{\text{rad}}^2 + a_{\text{tan}}^2}$

Chapter 6: Work and Energy

Work done by a constant force: $W = Fd \cos \theta$
 Kinetic energy: $K = \frac{1}{2}mv^2$
 Work-energy theorem: $W_{\text{tot}} = K_2 - K_1 = \Delta K$
 Power: $P = \Delta W / \Delta t$
 $P = Fv$
 Hooke's Law: $F_s = -kx$
 Work done by a spring: $W = \frac{1}{2}k(x_0^2 - x_f^2)$
 Work done by gravity: $W = -mg\Delta y$
 Gravitational potential energy: $U_g = mgh$
 Elastic potential energy: $U_E = \frac{1}{2}kx^2$
 Conservation: $(K + U_g + U_E)_0 + W_{\text{NC}} = (K + U_g + U_E)_f$

Chapter 7: Momentum, Impulse, and Collisions

Momentum: $\vec{p} = m\vec{v}$
 Force and momentum: $\vec{F} = (\vec{p}_f - \vec{p}_0) / \Delta t$ or $\Delta \vec{p} / \Delta t$
 Impulse: $\vec{J} = \vec{p}_f - \vec{p}_0 = m(\vec{v}_f - \vec{v}_0) = \vec{F}\Delta t$
 Conservation: $m_A \vec{v}_A + m_B \vec{v}_B + \dots = m_A \vec{v}_A' + m_B \vec{v}_B' + \dots$
 (\vec{v}_A' , \vec{v}_B' are post-collision final velocities)
 Completely inelastic collision: $m_A \vec{v}_A + m_B \vec{v}_B = (m_A + m_B) \vec{v}_f$
 1-D Elastic collision: $v_A + v_A' = v_B + v_B'$
 Center of mass: $x_{\text{CM}} = (m_1 x_1 + m_2 x_2 + \dots) / (m_1 + m_2 + \dots)$

Chapter 8: Rotational Motion, Part 1

Angular displacement: $\Delta \theta = \theta_f - \theta_0$
 Constant velocity: $\theta_f = \theta_0 + \omega t$ or $\Delta \theta = \omega t$
 Kinematics: $\omega_f = \omega_0 + \alpha t$
 $\Delta \theta = \omega_0 t + \frac{1}{2}\alpha t^2$
 $\omega_f^2 = \omega_0^2 + 2\alpha \Delta \theta$
 $\omega_f + \omega_0 = 2\Delta \theta / t$
 Velocity: $\omega_{\text{avg}} = (\theta_f - \theta_0) / (t_f - t_0)$
 Acceleration: $\alpha_{\text{avg}} = (\omega_f - \omega_0) / (t_f - t_0)$
 Angular \rightarrow tangential: $\Delta s = r\Delta \theta$, $v = r\omega$, $a = r\alpha$
 No-slip condition: $v_{\text{cm}} = R\omega$

Chapter 8: Rotational Motion, Part 2

Rotational KE:	$K_{\text{rot}} = \frac{1}{2}I\omega^2$
CM Moment of Inertia:	Point mass, mr^2 . Disk, $\frac{1}{2}mR^2$. Ring, mR^2 . Spherical shell, $\frac{2}{3}mR^2$. Sphere, $\frac{2}{5}mR^2$. Rod (about center), $\frac{1}{12}mL^2$
Parallel axis theorem:	$I = I_{\text{CM}} + md^2$
Torque (magnitude):	$\tau = rF \sin \theta$
Newton's 2nd Law:	$\tau_{\text{net}} = I\alpha$
Translational/rotational energy:	$K = \frac{1}{2}mv_{\text{cm}}^2 + \frac{1}{2}I_{\text{cm}}\omega^2$
Work done by constant torque:	$W = \tau\Delta\theta$
Work-energy theorem:	$W_{\text{tot}} = \frac{1}{2}I\omega_f^2 - \frac{1}{2}I\omega_0^2$
Angular momentum:	$\vec{L} = I\vec{\omega}$ (rigid body rotating about axis)
Conservation of angular momentum:	$I_A\omega_A + I_B\omega_B = I'_A\omega'_A + I'_B\omega'_B$ (primes indicate 'final')

Chapter 9: Static Equilibrium

Static equilibrium conditions:	$\vec{F}_{\text{net}} = 0$ $\tau_{\text{net}} = 0$ about any point
--------------------------------	---

Chapter 5: Gravitation

Gravitational constant:	$G = 6.67 \times 10^{-11} \text{ N}\cdot\text{m}^2/\text{kg}^2$
Mass of the Earth:	$M_E = 5.97 \times 10^{24} \text{ kg}$
Radius of the Earth:	$R_E = 6.38 \times 10^6 \text{ m}$
Force of gravity:	$F_G = GMm/r^2$
Local acceleration due to gravity:	$g = GM_E/R_E^2$
Orbits:	$v = 2\pi r/T$ $v^2 = GM/r$ $T^2 = 4\pi^2 r^3/(GM)$